

HSAJET® Micron MCHP1

Unique small controller and printer in one
ideal for repeat printing jobs



HP TIJ 2.5 technology

The HSAJET® Micron is based upon reliable HP TIJ 2.5 technology which delivers consistent, high-quality, fast printing, exceptional value, and ease of use. Micron is ideal for printing labels and for all cartons for food and pharmaceuticals. The possibilities are endless.

Load print job from USB-key

Build your print job on a PC using the free MicroDraw software delivered with the printer. Transfer to USB-key and connect to your Micron printer and you are ready to print. The layout can be saved to the internal memory and the USB-key may be removed.

Easy to integrate and use

The Micron is an 'out of the box' unit. Place an ink-cartridge in the head, connect to power and print instantly by pushing a button. The printer takes up very little space. Not much more than the actual print cartridge itself. This makes it very easy to integrate. Print horizontally or simply change the position of the printer 90° for printing vertically/down.

Built-in sensor

The Micron printer has an internal sensor. If external sensor is required connect this directly to the printer. The sensor distance is easily selected when designing the print job.

½" print height

The HSAJET® Micron runs with 1 HP print cartridge allowing a print height of 12.7 mm.

Ink Cartridges

A wide range of inks for each application are available: spot colors, UV inks or fast drying inks. The printer allows parameters settings for each ink to reach the best performance in all situations.

Prints in 300 x 300 dpi

- GRAPHICS
- TEXT (ALPHA NUMERIC)
- COUNTERS
- BARCODES (FIXED)*
- DATE & TIME (REAL-TIME & ADJUSTED)
- 3 WINDOWS TRUE TYPE FONTS

* For information on specific barcodes please go to www.hsasystems.com

Technical Details

HSAJET® MICRON MCHP1

Technology

HP TIJ 2.5

Print frequency

15 KHz

Print height

Up to 12.7 mm / ½"

Print heads

1 pen integrated

Print distance

0.5-2.0 mm (nozzle to print surface)

Voltage

15 V (power supply included)

Design software

MicroDraw (for WinPC)

Memory

1 print job in unit

Print features

Left/Right, Upside-down

Layout features

Max. length 2400 px (~10 cm in 600 dpi)

Unicode support in text

Object rotation (fixed): free

Object rotation (variable): 180 deg

Works with mm/inch/point/pixel

Interface

USB 2.0

Encoder input 3-33 V (SUB D9)

In-/Output 3-33 V (SUB D9)

Signals

Low ink signal (diode)

Print signal (diode)

Built-in sensor

Complies to

CE directives

Housing

Stainless steel

Weight

0.53 kg / 1.17 lbs

Resolution (DPI) (horizontal x vertical)	Max. speed	
	m / min	feet / min
300 x 300 1 row	76	250
150 x 300	152	500
75 x 300	304	1000

Resolution (Horizontal)

Different resolutions can be chosen between 50 and 600 dpi.

The maximum speed is affected by selection of horizontal resolution, since the frequency of the printhead remains the same.

75 dpi max 302 m/min to 600 dpi max 38 m/min.

Resolution (Vertical)


Save ink costs by removing lines from the printed image.

Available options are 300, 225, 200, and 150 DPI (0%, 25%, 33%, 50% ink reduction).




Notice that because of print height being just ½", the number of active dots are 150 to 75.

Accessories

- USB key (included)
- External sensor
- Encoder
- Bridges & Brackets
- Mountings (Inocon FLK18 mm included)



19.5 mm / 0.8"
Dist. to print nozzle



MCHP1-R

CHECK OUR WEBSITE FOR LATEST REVISION OF THIS DATASHEET

DISTRIBUTOR:



150 William Street
Perth Amboy, NJ 08861
Toll Free: 1-800-298-8936
Local: 1-732-324-0800
Fax: 1-732-324-4488
sales@hsausa.com
www.hsausa.com