

Ink for difficult substrates:

- Extra dark
- Sharp print on film substrates
- Long de-cap time
- Fast dry
- No need for heating device
- Highly reliable
- Printing on non-porous surfaces



# JR-001 Solvent Ink

**Extra Dark to print on non-porous substrates**

Cartridge Type	Thermal Inkjet 45Si Cartridge
Color	Black
Ink Type	Solvent based ink
De-cap Time	1 hour under normal conditions & environment
Printing Parameters	Voltage: 8.6V Pulse Width: 2.3us
Pulse Warm	OFF, Recommended
Shelf Life	6 month from fill date
Heater Requirements	No dryer necessary
Operating Condition	15°C~35°C
Storage Condition	15°C~35°C
Maximum Frequency	12kHz
Head Cleaning	Wipe with dry lint-free cloth. Do not clean with water.

## Ink Handling and Maintenance

Please clean (wipe) the print head before use.

- This product uses water-resistant dyes, but it is not recommended that printed materials are immersed in water.
- This product contains alcohol-based solvents. Should you feel unwell, ventilate the area well.
- If nozzles become blocked, wipe print head with a dry lint free wipe.
- Whenever the cartridge needs maintenance, place face down and wipe gently and lightly in the direction of the nozzles.
- Do not shake without a clip.
- Because print quality varies, depending on the application and environment, it is recommended that you test print on samples first.
- De-cap time is not guaranteed performance.
- It is not recommended to use in below 30% relative humidity

150 William Street  
Perth Amboy, NJ 08861  
Toll Free: 1-800-298-8936  
Phone: 732-324-0800  
Fax: 732-324-4488  
E-mail: sales@hsausa.com  
Web Site: www.hsausa.com

