

# HSAJET® TIPC15 Premium

TOUCH PRINT CONTROLLER FOR HP INKJET

Windows driven controller with  
database connectivity  
for fully variable imprints

## HSAJET® Premium Touch Printer Controller utilizes HP Thermal InkJet 2.5 technology

The Premium TIPC15 is the most compact stand alone touch controller available in the market that enables a print height of up to 100 mm (4").

The controller builds on the PCI express based HSAJET® CB6e controller board.

### Industrial casing

The black anodised aluminium frame and steel case provide extra protection for harsh industrial environments.

### HSAJET® software

The TIPC15 is delivered with Windows7 operating system and OBJ InkDraw printing software.

OBJ InkDraw is our software specially designed for coding/marketing applications.

All HSAJET® software solutions provide the features needed for their respective markets, including database connectivity and unique serialization capability, as well as an easy to use, intuitive design.

### Advanced software features

Stitching accuracy down to pixel level means printable objects can be located anywhere on the canvas without limitation.

All TIPC15 software packages offer a flexible ink saving feature providing up to a 75% ink saving in addition to fully variable resolution.

### Remote control

The comprehensive communication protocol allows you to control the unit remotely. Remote management is done through ethernet or serial connection.



**NEW**  
PREMIUM Touch  
Controller  
up to 100 mm  
Print Height

### Premium series

In addition to the TIPC15 Premium controller, we offer the Premium MiniTouch with a print height of 2" or the individually configured PC-controllers built on the CB6e controller board offering a print height of up to 8".

### Premium printhead

The centrepiece innovation of the Premium series is the hard anodised aluminium Premium printhead.

The printhead has a stainless steel footplate, which ensures that the printhead is completely free of static electricity. Ink cartridges are easy to replace and are held in the correct position without the use of a latch.

### Print at breakthrough speeds of up to 300 m/min in 300 x 150 dpi

- GRAPHICS
- COUNTERS
- SHIFT CODES
- VARIABLE TEXT
- FIXED TEXT
- LINEAR & 2D BARCODES\*
- DATE & TIME (REAL-TIME & ADJUSTED)
- WINDOWS FONTS

\* For information on specific barcodes please go to [www.hsasystems.com](http://www.hsasystems.com)

# Technical Details TIPC15-HP PREMIUM



## HSAJET TIPC15 PREMIUM TOUCH PRINT CONTROLLER

### Technology

HP TIJ 2.5

### Print height

Standard up to 2" (50.8 mm)  
with crypto key up to 4" (101.6 mm)

### Printheads

HSAJET® Premium printheads  
(see flyer)

Connect 2 printheads directly to the controller or use distributor box for connection of up to 8 single 1-pen printheads.

### Print distance

0.5-5.0 mm depending on ink and speed, typically 0.5-2.0 mm (nozzle to print surface)

### Voltage

100-240 VAC

### Print buffer

64 MB

### Screen

15" colour touch screen

### Design software

OBJ InkDraw (standard)  
Mail InkDraw (optional)

### Software menu language

English (multiple languages)

### Print functions, e.g.

Database printing (SQL - Txt - Access)  
User prompt  
User defined print log  
Error log

### Print options

Variable DPI  
Left/Right, Upside-down  
Other side, Bidirectional  
Inverted

### Layout options

Max. length 65000 px  
(~277 cm in 600 DPI)  
Object rotation in 90 deg intervals  
Link field content  
Works with mm/inch/point/pixel  
Unlimited number of objects

### Remote controlling via protocol

Start / stop print job  
Change field content per print  
Change print preferences/parameters

### Interface

RS232 (serial)  
Ethernet (LAN) 100 Mbit (Standard)  
USB 2.0  
Camera connection (USB)  
Control connection (SUB D15)  
Encoder Input 3-33V (SUB D9)  
In-/output 3-33 V (SUB D9)  
Printhead connections (2x RJ45)

### Complies with

CE directives

### Housing

Black anodised aluminium frame  
Stainless steel housing

### Weight

8.1 kg / 17.8 lbs

### Accessories


- Premium printheads (see other flyer)
- Distributor box
- USB Key / Stylus pen (included)
- Sensor and encoder
- Bridges & Brackets
- Mountings (Inocon 53 mm)
- Adaptorplate for Inocon FLV-25/ FLV-40/ FLS30-S1 (included)

Vertical resolution (DPI)	Horizontal resolution 75-2400 DPI (variable) speed examples (m/min)			
	75 DPI	300 DPI	600 DPI	2400 DPI
600 DPI	304	76	38	10
300 DPI high speed	608	152	76	19
300 DPI (row A)	304	76	38	10
300 DPI (row B)	304	76	38	10

TIPC15 Premium	PC configuration (min)
Hard disk	60 GB SSD disk
RAM	4 GB
Processor	Core i7-2720 3.3 Ghz
Printing Software	OBJ InkDraw Mail InkDraw
Operating System	Windows embedded Std 7 (WS7P) 32 bit
TIPC15 Premium	Dimension
Length	384 mm / 15.1"
Width	106 mm / 4.2"
Height	294 mm / 11.6"



Distributor box



CHECK OUR WEBSITE FOR THE LATEST VERSION OF THIS DATASHEET

DISTRIBUTOR:



The first choice in package printing.

150 William Street  
Perth Amboy, NJ 08861  
Toll Free: 1-800-298-8936  
Local: 1-732-324-0800  
Fax: 1-732-324-4488  
sales@hsausa.com  
www.hsausa.com